

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau


INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification: A47J 37/06		(11) International Publication Number: WO 99/07267
A1		(43) International Publication Date: 18 February 1999 (18.02.99)
(21) International Application Number: PCT/CA98/00763 (22) International Filing Date: 7 August 1998 (07.08.98) (30) Priority Data: 2,211,495 8 August 1997 (08.08.97) CA (71) Applicant (for all designated States except US): WOOD-FLAME INC. [CA/CA]; 910 Boulevard Industriel, Saint-Jean-sur-Richelieu, Québec J3B 8J4 (CA). (72) Inventor; and (75) Inventor/Applicant (for US only): PATENAUDE, Jean-Pierre [CA/CA]; 1738 route 132, St-Anicet, Québec J0S 1M0 (CA). (74) Agent: ROBIC; 55 Saint-Jacques, Montréal, Québec H2Y 3X2 (CA).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published With international search report.

(54) Title: COOKING APPARATUS AND GRILL ASSEMBLY THEREOF

(57) Abstract

The grill assembly (12) comprises a housing (30) including a cooking surface (32), sidewalls (34) skirting the cooking surface (32) and a bottom wall (36) including an inlet (38) adapted to be sealingly connected to a source of heat to prevent heat loss and to promote collection of the heat in the housing (30). The cooking surface (32) comprises a base plate (42) and a plurality of parallel ridges (40) projecting from the base plate (42) for supporting food to be cooked and spacing the same from the base plate (42), thereby allowing the food to be cooked by radiation and conduction. The base plate (42) is provided with a plurality of slits (46) located between the ridges (40) for allowing a flow of hot gases through the base plate (42) and the food to be also cooked by convection. A support (16) is provided to support the housing (30) over a source of heat. This invention reduces heat required and provides a means for controlling different types of heat transfer.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BI	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

WO 99/07267

PCT/CA98/00763

COOKING APPARATUS AND GRILL ASSEMBLY THEREOF

FIELD OF THE INVENTION

5 The present invention relates generally to the field of cooking apparatus and accessories thereof. More particularly, it relates to a grill assembly for a cooking apparatus that improves heat transfer and provides taste cooking by radiation, conduction and convection at the same time.

BACKGROUND OF THE INVENTION

10 The present invention relates to an arrangement of a means to collect heat and to transfer it to cook food. It is a compact one piece assembly acting as a heat retainer and transfer. It collects, gathers and provides, through the
15 arrangement of its components, selective heat transfer process from a heat source to the food to be cooked. Cooking is a transformation process whereby the heat modifies food for consumption. The transformation process involves or is affected by temperature, time, equipment and medium. Food cooking is
20 done for appearance, flavour and sometimes conservation. The processes of heat transfer are radiation, conduction and convection, each process having its own characteristics and producing specific transformation of the food in its structure, appearance and flavour. Cooking process involves heat
25 consumption. Considering a heat saving in this field would amount to huge saving. This invention has been conceived to operate with a flame burner as the heat source because it is the most widely used. However, it could easily be adapted to different heat sources.

30 Well known in the field of grills used with cooking apparatus, there is obviously the typical grill which consists of an assembly of parallel metal bars that is placed over any type of source of heat and that serves to support the food over the heat. A drawback with that type of grill which is commonly
35 used in ovens, with portable stoves used in camping or with outdoor barbecues is that it allows the food to be cooked randomly by convection and a little bit by conduction and by

WO 99/07267

PCT/CA98/00763

2

radiation. In other words, they lack of control over convection, conduction and radiation. Also the cooking apparatus which uses that type of grill are generally not adapted or are not designed for saving energy. A lot of heat produced is lost with that type of grill and cooking apparatus.

There is still presently a need for an energy saving grill that will allow food to be cooked at the same time by conduction, convection and radiation on a ratio base to obtain a special taste.

SUMMARY OF THE INVENTION

An object of the present invention is to propose a grill assembly for a cooking apparatus that will satisfy the above-mentioned needs.

In accordance with the present invention, that object is achieved with a grill assembly characterized in that it comprises a housing including a cooking surface, sidewalls skirting the cooking surface and a bottom wall including an inlet adapted to be tightly connected to a source of heat to prevent heat loss and to promote collection of the heat in the housing. The grill assembly is further characterized in that the cooking surface is made of metal and comprises a base plate and a plurality of parallel ridges projecting from the base surface for supporting food to be cooked and spacing the same from the base plate, thereby allowing the food to be-cooked by radiation and conduction. The base plate is provided with a plurality of slits located between the ridges for allowing a flow of hot gases through the base plate and the food to be also cooked by convection. A support is provided to support the housing over a source of heat.

This grill assembly, because of its specific characteristics, provides heat transfer from the heat source to the food in an energy saving manner while allowing the food to be cooked by radiation, conduction and convection.

Another object of the present invention is to propose a cooking apparatus that comprises a grill assembly as described hereinbefore.

WO 99/07267

PCT/CA98/00763

3

A cooking apparatus including a grill assembly according to a preferred embodiment of the present invention will now be described in more details with reference to the appended drawings.

5

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a cross-sectional side elevational view of a cooking apparatus including a grill assembly according to the present invention.

10 Figure 2 is a cross-sectional front elevational view of the cooking apparatus of figure 1.

Figure 3 is an enlarged perspective partly cut view of a half unit of the grill assembly of figure 1.

15 Figure 4 is a cross-sectional side view of a grill assembly similar to the one of figure 1 shown without the deflector and the handle.

DESCRIPTION OF A PREFERRED EMBODIMENT

Referring to figures 1 and 2, the cooking apparatus (10) in a general manner comprises a grill assembly (12), a tubular burner (14) and a support to mount the grill assembly (12) over the burner (14) and which preferably consists of an open container (16) adapted to receive therein the burner (14) in an upright position. As can be appreciated, in this preferred embodiment, the burner (14) is mounted on a dome-shaped member (79) set on the bottom wall (17) of the container (16). The dome-shaped member (79) with the bottom wall (17) of the container (16) are defining an air-receiving chamber (70) devised to provide air in the combustion chamber (60) for the combustion of a fuel therein. A pump means (74) is connected to the air-receiving chamber via a conduit (72). The container (16) has sidewalls (18) each having an upper edge (20) adapted to receive and support a corresponding outer edge (22) of the grill assembly (12) such that the grill (12) is mountable over the burner (14) which is enclosed in the container (16). More particularly, the upper edge (20) of each of the sidewalls (18)

WO 99/07267

PCT/CA98/00763

4

defines an L-shaped shoulder on which a corresponding outer edge (22) of the grill (12) is resting.

Referring now also to figures 3 and 4, the grill assembly (12) comprises a housing (30) including a cooking surface (32), sidewalls (34) skirting the cooking surface (32) and a bottom wall (36). The bottom wall (36) includes an inlet (38) which is preferably a circular aperture provided in that bottom wall (36) adapted to be tightly connected to the upper edge (15) of the burner (14) from which the heat is exiting to prevent heat loss and to promote collection of the heat in the housing (30). In other words, the edge (15) or contour of the burner (14) is fitting close in the circular aperture (39) of the bottom wall (38). In this manner, almost no heat from the burner is lost as it is transferred to the housing (30).

As can be appreciated from figure 1, the grill assembly (12), which is particularly adapted to be used with a portable stove, consists of two half units (12a,12b) that together constitute the whole grill assembly (12). However, the grill assembly may very well consist of a single unit, as shown in figure 4.

Referring to figures 3 and 4, the cooking surface (32) is made of metal, preferably stainless steel and comprises a base plate (42) and a plurality of parallel ridges (40) projecting from the base plate (42) for supporting food (44) to be cooked and spacing the same from the base plate (42), thereby allowing the food to be cooked by radiation and conduction. The base plate (42) is provided with a plurality of slits (46), as best seen in figure 3, located between the ridges (40) for allowing a flow of hot gases, as shown in figure 4, through the base plate (42) and the food to be also cooked by convection.

More preferably, the cooking surface (32) consists of a corrugated metallic plate comprising ridges (40) having an apex (41) of a given width allowing the food (44) to be cooked by conduction, the ridges (40) alternating with grooves forming the base plate (42).

As shown in figure 3, in order to obtain a uniform cooking, the slits (46) are disposed in rows in the base plate

WO 99/07267

PCT/CA98/00763

5

(12). Moreover, each slit (46) is preferably transversely filling the space defined between two adjacent ridges (40).

As can be appreciated from figure 4, as the grill assembly (12) is positioned over the burner (14) in a sealed manner, the heat from the burner (14) (not shown) is directly transferred to the cooking surface (32) of the grill assembly (12) and then it is transferred from the cooking surface (32) to the food (44) by radiation from the base plate (42), by conduction from the apex of the ridges (40) and by convection from the flow of hot gases through the base plate (42) via the slits (46) therein.

In order to further improve the heat transfer and the cooking process, the grill assembly (12) illustrated further comprises a deflector (50) within the housing (30), as best shown in figures 1 and 2, mounted above the inlet (38) of the bottom wall (36) to buffer and distribute a flow of gas from the heat source. The deflector (50) spread and elongate the gas fuel in store to allow a spread combustion. Preferably, the deflector (50) is a convex metallic plate extending centrally and transversely within the housing (30).

The cooking surface (32), the sidewalls (34) and the bottom wall (36) of the grill assembly (12) are preferably made of a metal of poor thermal conductivity, most preferably stainless steel.

For a practical point of view, the grill assembly (12) may advantageously include handles (52), as shown in figure 1.

As can be appreciated, the grill assembly acts as a heat retainer and transfer device which collects most of the heat and promotes specific heat transfer process to the food to be cooked. This invention reduces heat required and improves heat transfer in cooking.

With a grill assembly device according to the present invention, the food is cooked through conduction by contact with a support surface heated by convection, through convection in a direct manner from a flow of gases and through radiation in a direct manner from the plate.

WO 99/07267

PCT/CA98/00763

6

WHAT IS CLAIMED IS:

1. A grill assembly (12) characterized in that it comprises:

5 a housing (30) including:

a cooking surface (32),

sidewalls (34) skirting the cooking surface (32); and

10 a bottom wall (36) including an inlet (38) adapted to be tightly connected to a source of heat to prevent heat loss and to promote collection of the heat in the housing (30);

the cooking surface (32) comprising:

15 a base plate (42) and a plurality of parallel ridges (40) projecting from the base plate (42) for supporting food to be cooked and spacing the same from the base plate (42), thereby allowing the food to be cooked by radiation and conduction, the base plate (42) being provided with a plurality of slits (46) located between the ridges (40) for allowing a flow of hot gases through the base plate (42) and the food to be also cooked by convection and radiation; and

20 a support to support the housing (30) over a source of heat.

25 2. A grill assembly (12) according to claim 1, characterized in that the cooking surface (32) is a corrugated metallic plate comprising the ridges (40) having an apex (41) of a given width allowing the food to be cooked by conduction alternating with grooves forming the base plate (42).

30 3. A grill assembly (12) according to claim 2, characterized in that each of the slits (46) in the metallic plate (42) is transversely filling a space between two adjacent ridges (40).

35 4. A grill assembly (12) according to anyone of claims 1 to 3, characterized in that the cooking surface (32), the sidewalls (34) and the bottom wall (36) are made of stainless steel.

WO 99/07267

PCT/CA98/00763

7

5. A grill assembly (12) according to anyone of claims 1 to 4, characterized in that it further comprises a deflector (50) within the housing (30), mounted above the inlet (38) of the bottom wall (36) to buffer and distribute a flow of gas from the heat source.

6. A grill assembly (12) according to claim 5, characterized in that the deflector (50) is a convex metallic plate extending centrally and transversely within the housing (30).

7. A grill assembly (12) according to anyone of claims 1 to 6, characterized in that the inlet (38) of the bottom wall (36) is a circular aperture provided therein.

8. A grill assembly (12) according to anyone of claims 1 to 7, characterized in that the grill assembly (12) consists of two half units (12a,12b) that together constitute the whole grill assembly (12).

9. A cooking apparatus (10) characterized in that it comprises:
a grill assembly (12) as defined in anyone of claims 1 to 8; and

a tubular burner (14) having an upper edge sealingly connectable with the inlet (38) of the bottom wall (36) of the grill assembly (12).

10. A cooking apparatus (10) according to claim 9, characterized in that the support comprises an open container (16) adapted to receive therein the burner (14) in an upright position, the container (16) having sidewalls (18) each having an upper edge (20) adapted to receive and support a corresponding outer edge (22) of the grill assembly (12) such that the grill assembly (12) is mountable over the burner (14) enclosed in the container (16).

WO 99/07267

PCT/CA98/00763

1 / 4




FIG. 1

SUBSTITUTE SHEET (RULE 26)

WO 99/07267

PCT/CA98/00763

2 / 4




FIG. 2

SUBSTITUTE SHEET (RULE 26)

WO 99/07267

PCT/CA98/00763

3 / 4




FIG. 3

SUBSTITUTE SHEET (RULE 26)

WO 99/07267

PCT/CA98/00763

4 / 4




FIG. 4

SUBSTITUTE SHEET (RULE 25)

INTERNATIONAL SEARCH REPORT

International Application No

PCT/CA 98/00763

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 A47J37/06

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 6 A47J

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 647 339 A (EZRA SHALOM) 15 July 1997	1-4,7,9, 10
Y	see column 1, line 29 - column 2, line 12; figures 1-3,7,9	5,6
Y	WO 89 11066 A (HERTFORD PTY LTD) 16 November 1989 see page 6, line 21 - page 6, line 32; figure 1	5,6
X	US 5 105 725 A (HAGLUND ALLEN C) 21 April 1992	1-4,7,9, 10
Y	see column 1, line 1 - column 4, line 9; figures 1,2,7	8
Y	US 4 936 202 A (LIN PAUL) 26 June 1990 see abstract; figure 2	8
-/--		

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in Annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- *Z* document member of the same patent family

Date of the actual completion of the international search

19 November 1998

Date of mailing of the international search report

26/11/1998

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel: (+31-70) 340-2040, Tx: 31 651 epo nl
Fax: (+31-70) 340-3016

Authorized officer

Acerbis, G

INTERNATIONAL SEARCH REPORT

Internat'l Application No.

PCT/CA 98/00763

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 355 780 A (CAMPBELL MICHAEL F) 18 October 1994	1-3,7,9
A	see column 1, line 1 - column 3, line 56; figures	10
A	US 4 403 541 A (BERGER BERNARD B) 13 September 1983 see column 1, line 25 - column 2, line 53; figures 1,2	1-10

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/CA 98/00763

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5647339	A	15-07-1997	US 5806509 A	15-09-1998
WO 8911066	A	16-11-1989	CA 1320402 A	20-07-1993
			AU 3730389 A	29-11-1989
			EP 0414794 A	06-03-1991
US 5105725	A	21-04-1992	NONE	
US 4936202	A	26-06-1990	NONE	
US 5355780	A	18-10-1994	CA 2116905 A,C	10-09-1994
US 4403541	A	13-09-1983	CA 1108954 A	15-09-1981
			US RE32288 E	18-11-1986

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

☐ BLACK BORDERS

☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES

☒ FADED TEXT OR DRAWING

☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING

☐ SKEWED/SLANTED IMAGES

☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS

☐ GRAY SCALE DOCUMENTS

☒ LINES OR MARKS ON ORIGINAL DOCUMENT

☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY

☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.